



**NOTES:**

1. NAILS MEET MIN. BEND YIELD REQUIREMENT OF 100,000 PSI

S80-FH	2.000	.1185	.240
S80GAL-FH	2.000	.1185	.240
S80-FH	2.375	.118	.245
S80GAL-FH	2.375	.118	.245
S100-FH	3.000	.129	.250
S100GAL-FH	3.000	.129	.250
S120-FH	3.250	.118	.245
S120GAL-FH	3.250	.118	.245
S120131-FH	3.250	.129	.250
S120131GAL-FH	3.250	.129	.250
S160131-FH	3.500	.129	.250
S160131GAL-FH	3.500	.129	.250

**TABULATION**

B ADD S160131-FH, UPDATE WIRE #		60304	REV 3/28/12	REV 3/28/12	REV 3/28/12
REV.	DESCRIPTION	PROD. NO.	ORIG./ST.	UPD./ST.	DRG./ST.
DATE	BY	REASON	DATE		
CUSTOMER REFERENCE DRAWING		DO NOT SCALE - WORK TO DIMENSIONS ONLY ALL DIMENSIONS ARE IN INCHES			
NOTE: ALL DIMENSIONS AND SPECIFICATIONS ARE NOMINAL.		 A Division of The Stanley Works East Greenwich, RI 02818 U.S.A.			
DESCRIPTION		OSRH PLAIN SHANK NAIL			
DRAWING NUMBER		175449			REV. B